



... for Your packaging

**STRAPPING
MACHINERY**

IP65

**Unparalleled performance, innovative features,
and a great price.**


The SM65 is, quite simply, the best value available in today's marketplace for strapping machines. At 65 straps per minute, it is lightning fast. Available in several different arch and strap sizes, the SM65 is an excellent strapper for a broad range of applications. The state of the art strapping head has 30% fewer parts than comparable strapping machines, and utilizes brushless DC motors. The result is a high speed strapping machine that consumes less power, requires fewer adjustments, and minimal maintenance. The extensive list of standard features on the SM65 is listed below. Plus, it's backed by the best warranty in the industry, 99% parts availability within 24 hours, and unlimited, free telephone support for the life of the machine. If you are looking for a fast, reliable strapper that is operator and maintenance friendly, you can't get a better value than the SM65.

Standard Features of the SM65 include:

- **Patented Easy Strap Access**
Access to the strapping channel requires no tools
- **One Piece Strap Track**
Track design eliminates dusting and guarantees parallel straps
- **Quick Coil Change**
Strap is changed at waist height and automatically fed, no more crawling on the floor
- **Sensor Controlled Heater**
Heat seals are consistent and highly reliable
- **Jam Free Technology**
Missed straps are ejected and the SM65 returns to the ready position
- **Adjustable Table Height**
The table height is adjustable to any height between 32.3" and 36.2" (820mm-920mm)
- **Photocell Activation**
Several options can be programmed when this feature is activated
- **Pivoting Control Panel**
Allows the operator to access the control panel from either side of the machine
- **Machines 850mm and wider have standard rollertables**
- **Machines set for 12mm strap have external strap reel**

Options Available on the SM65:

- Foot pedal switch
- Available in a Stainless Steel Frame
- Machines 550mm and 650mm wide are available with roller tables





... for Your packaging

TECHNICAL SPECIFICATIONS

All dimensions refer to an arch size of 25.6" (650mm) wide x 19.7" (500mm) high.

- Dimensions:** 48"W x 25.6"D x 55.3" - 59.25"H
1220mmW x 650mmD x 1405-1505mmH
- Weight:** 352 lbs.
160kg.
- Table Height:** 32.3" - 36.2" (adjustable)
820mm - 920mm
- Tension Range:** 5-6mm
2-77 lbs.
1-35Kg
9-12mm
2-100 lbs.
1-45Kg
- Package Size:** Minimum: 2.75"W x .75"H
70mm x 20mm
Maximum: Dependent upon arch size
- Speed:** Up to 65 Straps per minute
- Strap Size:** 1/4", 3/8", 1/2"
- Core Size:** 8" x 8"
200mm x 200mm
- Power Requirements:** 110V, Single phase 50/60 Hz,
5 Amps, 230V available as an option

STRAPPING MACHINERY

Arch Sizes - SM65, 1/4", 3/8" (5,6, and 9mm)

Width: In/mm 21.6/550 25.6/650 33.4/850 41.3/1050 49.2/1250 64.9/1650 72.8/1850 80.7/2050 88.6/2250

Height: In/mm

15.7/400			X						
19.7/500	S		X		X	X			
23.6/600		X	X						
31.5/800			X	X	X		X		
39.4/1000				X	X				

S indicates standard size

Arch Sizes - SM65 1/2" (12mm)

Width: In/mm 21.6/550 25.6/650 33.4/850 41.3/1050 49.2/1250 64.9/1650 72.8/1850 80.7/2050 88.6/2250

Height: In/mm

15.7/400			X						
19.7/500		S				X		X	
23.6/600			X	X	X				X
31.5/800			X	X	X		X		
39.4/1000			X	X	X				

S indicates standard size





... for Your packaging

**STRAPPING
MACHINERY**

