

STRAPPING MACHINERY

Strapper Impact

Uniquely designed to outperform traditional semi-automatic strappers...



... for Your packaging

The impact semi automatic strapper utilizes state-of-the-art technology to give you a machine that is durable, reliable and affordable. The simplistic design of the Impact eliminates chains, belts and pulleys, dramatically reducing repair expenses and costly down time.

Standard features of the Impact Strapper Include:

- **Adjustable Welding Time**
Efficient seals, even under extremely high tension.
- **Electronic Tension Control**
Consistent, exact tension, with a range of 17 to 100lbs.
- **24 Volt Power**
Unparalleled safety.
- **Direct Drive**
All drive belts, chains and pulleys are eliminated, reducing repair and maintenance costs.
- **Unique Frame**
A full size, durable frame, which adjusts to your working height.

The Impact is also available with the following optional features:

- A digital readout for tension and feed setting
- A small package option
- A low tension option



TECHNICAL SPECIFICATIONS

Dimensions:	33.4"L x 22"D x 30.7"H to 37.4"H (adjustable)
Package Size:	Minimum - 3¼"W x 1¼"H 1¾"x1" (with small package option) Maximum - Unlimited
Tension Range:	17 - 100 lbs. 12 - 100 lbs. (with low tension option)
Speed:	2.5 seconds per cycle
Weight:	155 lbs.
Core Size:	8x8, 9x8
Strap Size:	1/4", 5mm - 1/2", 13mm
Power Requirements:	110V, 50/60 Hz